

Specification

| | |
|----------------------------------|---|
| Power supply | 400v / 28A / 50Hz (other on request) |
| Power | 18kW |
| Steam production | 30kg/hr, 188oC in the boiler, 12 bar pressure |
| Temperature at the nozzle | 150oC |
| Water feeding | by water network |
| Water descaler | YES |
| Functions for grip handle | Steam / steam & detergent / steam & water |
| Detergent tank | 5 litre |
| Indicator for lack of water | YES |
| Indicator for lack of detergent | YES |
| Adjustable quantity of detergent | YES |
| Maximum hose length | 12m |
| Weight | 230kg |
| Dimensions | 400 x 1300 x 1600mm |

Machine equipped with

Heavy duty professional saturated steam cleaning unit with 18kW generator

For industrial, food processing and cleaning including degreasing, sanitising and disinfecting

Preparation of surface treatments including phosphate coating and passivation

Adjustable detergent mixture

Stainless steel (AISI 304) body

2 x electronically controlled 9.0kW boilers

Three functions available from the grip handle :-

Steam / steam & detergent / steam & water

Low voltage circuitry for operator safety including 12 volt hand nozzle

Water descaler filter

Starts in less than 4 minutes

No water indicator

No detergent indicator

CE, PED, IPX 5 certifications

Options include:

Automatic boiler drain kit, additional chemical tank, water softener, hot water kit, customer PLC control kit