

- 2D/3D Graphic Controls with automatic bending sequence calculation
- Automatic generation of the bending program and Auto Tooling
- First-rate consistent angle accuracy by means of mechanical crowning
- Choice of high-accurate backgauge systems
- Compatible with European Standard (ES) and New Standard (NS) tooling systems
- Capacity from 750 up to 3200kN, Bending Length from 2000 up to 6000mm

Standard Equipment

- Capacity from 750 up to 3200kN, Bending Length from 2000 up to 6000mm
- FastBEND-2D Premium Graphic Control with 15" Touch Screen
- Fast X/R backgauge on ball screws
- Fast Approach Speed 200mm/s (models up to 2000kN)
- Stroke X-axis = 800mm, speed = 1000mm/s (models up to 4m and 2500kN)
- Stroke R-axis = 130mm (models up to 4m and 2500kN)
- European Standard toptooling with Quick Manual Clamping arrangement
- Manual Adjustable Crowning Table for European
- Standard tooling

Options Include

- HacoBend-2D Offline Software
- More-axes backgauge systems : X-R-Z/Z', X-R-Z1/Z2, X3
- Increased Daylight Opening (+170mm) and Stroke (+170mm)
- New Standard tooling (Wila)
- Movable Sheet Supports
- Optical Guarding systems (DSP, Lazersafe, Fiessler, ...)