

## Haco Fixed Angle Hydraulic Notcher

**Specifications**

Capacity Mild Steel (450N/mm <sup>2</sup> )	<b>MAXI 250/6</b> 6mm
Capacity Mild Steel (450N/mm <sup>2</sup> ) at 60 degrees	N/A
Blade Length	250mm
Angle	90o Deg
Strokes per minute	35
Table dimensions	900 x 700mm
Motor power	3kW
Overall dimensions	900 x 920 x 1100mm
Weight	800kg

**Standard Equipment**

Hydraulic angle notching machine with fixed angle 90 degrees **(Mini 220/4 & Maxi 250/6)**  
Hydraulic angle notching machine with fixed angle 30-140 degrees **(Vari 220/6 - Combi 220/6)**  
Automatic blade gap adjustment  
2 position stops with scale, adjustment ever 15 Degrees, clamping handle for intermediate positions  
2 mechanical plate hold downs  
Large working table with slots and brass scales  
60 Degrees negative blades to cut stainless steel  
Mechanical vertical stroke adjuster with readout  
Mechanical stroke adjuster  
Transparent hand safety guards  
Internal stop with millimetric scale  
Foot pedal control  
Hydraulic oil

**Extra Workstation On Combi 220/6**

Cavity to accept punching, rectangular notching and bending tooling  
Bending speed adjustment from 0-10mm/s  
Back gauge for bending operations  
Adjustment of working pressure  
Working table with slots  
Press capacity 200kN  
Millimetric scales  
Transparent hand safety guard

**(Vari 220/6 - Combi 220/6)**  
**(Vari 220/6 - Combi 220/6)**  
**(Mini 220/4 & Maxi 250/6)**

## Haco Fixed Angle Hydraulic Notcher