

Specifications

Bar diameter	5-65mm
Bar length*	150-1540mm
Magazine capacity	550mm
Drive	Servo Motor
Height range	850mm to 1260mm
Weight	430kgs
Voltage	230/415v max

*For bars longer than headstock length a Bar Support Unit is required

Standard Features

Servo control
Part programme storage
Standard bar diameter range 5-65mm
Floor mounted sliding rails
Bar position accuracy to 0.1mm
Bar length measurement
Random bar lengths accepted from 150mm
Barfeed or shaft load
Controlled feed
Quick and easy set-up
User-friendly HMI screen
CE Certified
Additional features available to optimise your cycle time

Standard

Bar Capacity

The Multifeed 65 will cater for bar diameters from 5mm to 65mm diameter.

HMI screen

The operator friendly HMI screen gives you the flexibility to increase the automation of the Multifeed 65 to suit your manufacturing requirements.

Floor mounted sliding rails

The Multifeed 65 is fixed to floor mounted sliding rails, allowing the operator to move the Barfeed away from the machine tool in the Z axis. Once the Barfeed has been moved, the machine tool can be accessed safely.

The Multifeed 65 package includes:

Liner system

3 pushrods: 6mm, 12mm and 18mm diameter

Interface cable

Delivery

Installation

Operator training on day of installation

Full after sales support