

Specification

Electrical supply	BNA 105 400 Volt, 3 Phase
Motor	1.1Kw
Motor speed	1400 & 2800 rpm
Wheel speed	15 & 30 m/s
Grinding wheel size Diameter x width	200 x 25mm
Spindle adaptor	20mm
HD Bolt centres	500CRS to suit 2 - 8mm Bolts
Weight	110Kg
	BNA 106
Electrical supply	400 Volt, 3 Phase
Motor	1.5Kw
Motor speed	1400 rpm
Wheel speed	18 m/s
Grinding wheel size Diameter x width	250 x 30mm
Spindle adaptor	25mm
HD Bolt centres	500CRS to suit 2 - 8mm Bolts
Weight	115Kg
	BNA 107
Electrical supply	400 Volt, 3 Phase
Motor	1.8Kw
Motor speed	1400 rpm
Wheel speed	22 m/s
Grinding wheel size Diameter x width	300 x 35mm
Spindle adaptor	30mm
HD Bolt centres	500CRS to suit 2 - 8mm Bolts
Weight	130Kg

Key Features

- Fabricated base
- Dust extraction spigots – 80mm outside diameter (60mm overall dia for BNA105)

Adjustable work rest
Supplied with two grinding wheels
Water tray
Tool cupboard in pedestal

Safety Features

Motor braking system
No volt overload push button controls
Emergency stop
Mechanical guard lock
Eye shields
Low noise level only 69db

Optional Refinements

Remote dust extraction to enable compliance with UK COSHH Regulations
Remote foot stop safety switch