

**Machine Specifications****600E**

Maximum distance between centres	630mm
Maximum grinding length	630mm
Height of centres over table	180mm
Swing over table	355mm

**1000E**

Maximum distance between centres	1030mm
Maximum grinding length	1030mm
Height of centres over table	180mm
Swing over table	355mm

**1500E**

Maximum distance between centres	1530mm
Maximum grinding length	1530mm
Height of centres over table	180mm
Swing over table	355mm

**2000E**

Maximum distance between centres	2030mm
Maximum grinding length	2030mm
Height of centres over table	180mm
Swing over table	355mm

**Machine is equipped with**

Table manual swivelling system for taper grinding with dial gauge

Electric installation 24V

Hydraulic unit complete (without oil)

Pneumatic unit

Centralized lubrication

**Standard Equipment**

Coolant equipment complete with pump, tank, pipes and nozzle

Straight wheel dressing unit mounted on tailstock (diamond optional)

Grinding wheel diam. mm. 450, thickness mm. 50, hole mm. 127

Grinding wheel flange  
Micrometric device for table traverse stop  
Wheel balancing arbor  
Wheel extractor  
Additional pulley for wheel motor  
2 hard metal tipped centers  
Set of levelling screws and plates  
2 cloth bellows for table guide protection  
Sliding doors  
Set of service spanners & Set of hexagonal spanners  
5 Kg. oil for wheel spindle lubrication & 5 Kg. oil for guide lubricating  
Instructions manual