

Machine Specifications 1500GE T6

Maximum distance between centres	1950mm
Maximum grinding length	1600mm
Height of centres over table	300mm
Swing over table	595mm

2000GE T6

Maximum distance between centres	2450mm
Maximum grinding length	2100mm
Height of centres over table	300mm
Swing over table	595mm

3000GE T6

Maximum distance between centres	3450mm
Maximum grinding length	3100mm
Height of centres over table	300mm
Swing over table	595mm

Machine is equipped with:

SIEMENS TP700 touch screen control panel
Wheel head and table automatic electronic feed controlled by motor brushless
Incremental optic rule for micro positioning of wheel head
Re-circulating ball screw with preloaded nut for wheel head and table movement
Anti-friction material on wheel head guides
Electric installation, in separate cabinet
Hydraulic unit for tailstock control
Pneumatic unit
Centralized lubrication

Standard Equipment

Coolant equipment complete with pump, tank pipes and nozzle
Straight wheel dressing unit (diamond optional) mounted on tailstock
Grinding wheel diameter 610mm, thickness 80mm, hole 203mm
Grinding wheel flange

Robbi Omicron Semi Automatic GE T6 Series Plain External Grinding Machines

Wheel balancing arbor

Wheel extractor

Additional pulley for wheel motor

2 hard metal tipped centres

Set of levelling screws and plates

2 cloth bellows for table guide protection

Sliding doors

Set of service spanners & Set of hexagonal spanners

5 Kg. oil for wheel spindle lubrication & 5 Kg. oil for guide lubricating

Instructions manual