

<b>Machine Specifications</b>	<b>600RT6</b>
Maximum distance between centres	600mm
Maximum grinding length	600mm
Height of centres over table	160mm
Swing over table	315mm
	<b>1000RT6</b>
Maximum distance between centres	1000mm
Maximum grinding length	1000mm
Height of centres over table	160mm
Swing over table	315mm

**Machine is equipped with:**

PRO-FACE touch screen control panel  
Wheel head and table automatic electronic feed controlled by motor brushless  
Incremental optic rule for micro positioning of wheel head  
Table manual swivelling system for taper grinding with dial gauge  
Re-circulating ball screw with preloaded nut for wheel head and table movement  
Anti-friction material on wheel head guides  
Electric installation, in separate cabinet  
Pneumatic unit  
Centralized lubrication

**Standard Equipment**

Coolant equipment complete with pump, tank, pipes and nozzle  
Straight wheel dressing unit (diamond optional) mounted on tailstock  
Grinding wheel diam. mm. 450, thickness mm. 50, hole mm. 127  
Grinding wheel flange  
Wheel balancing arbor  
Wheel extractor  
Additional pulley for wheel motor  
2 hard metal tipped centres  
Set of levelling screws and plates

2 cloth bellows for table guide protection

Sliding doors on base

Set of service spanners & Set of hexagonal spanners

5 Kg. oil for wheel spindle lubrication & 5 Kg. oil for guide lubricating

Instructions manual