

Specification

| | |
|---------------------------------|----------------------------|
| Centre height | 500mm |
| Swing over bed diameter | 1000mm |
| Swing over cross slide diameter | 620mm |
| Spindle bore | 160mm (230mm option) |
| Spindle range | 0-800rpm (0-500rpm option) |

TITANO T 500

| | |
|---------------------------------|----------------------------|
| Centre height | 550mm |
| Swing over bed diameter | 1100mm |
| Swing over cross slide diameter | 720mm |
| Spindle bore | 160mm (230mm option) |
| Spindle range | 0-800rpm (0-500rpm option) |

TITANO T 550

| | |
|---------------------------------|----------------------------|
| Centre height | 600mm |
| Swing over bed diameter | 1200mm |
| Swing over cross slide diameter | 820mm |
| Spindle bore | 160mm (230mm option) |
| Spindle range | 0-800rpm (0-500rpm option) |

TITANO T 600

| | |
|---------------------------------|----------------------------|
| Centre height | 650mm |
| Swing over bed diameter | 1300mm |
| Swing over cross slide diameter | 920mm |
| Spindle bore | 160mm (230mm option) |
| Spindle range | 0-800rpm (0-500rpm option) |

TITANO T 660

| | |
|---------------------------------|----------------------------|
| Centre height | 700mm |
| Swing over bed diameter | 1400mm |
| Swing over cross slide diameter | 1020mm |
| Spindle bore | 160mm (230mm option) |
| Spindle range | 0-800rpm (0-500rpm option) |

TITANO T 700

Machine Features

ROHM ZG Cast Iron 3 Jaw chuck - 500mm dia, 190mm bore
ROHM UGU IND 4 jaw chuck - 630mm dia, 160mm bore (400rpm max)
Quick change toolpost and 5-off holders Type D
Drive and servomotor SIEMENS for regulation speed with potentiometer
Digital rpm readout
Rapid traverse controls
Dead centres
Full rear splash guard with lamp
Taper spindle reducing bush - Series of set screw wrenches
Series of set screw wrenches
Oil lubrication system by an automatic pump with timer
Motor driver pump and coolant system
Safety screen
Levers and handwheels matt chromium plated