MACHINE SPECIFICATION	Europa 2013 V Vertical Bandsaws
Unitized frame	arc welded steel
Throat: band to column	508mm
Max. work height	330mm
Band width capacity	
Model: V2	1,5 to 27mm
Model: V3	3 to 27mm
Saw band length	3910mm
Table	660 x 660mm
Table tilt	45° r, 10° l.
Var. tool speed	10-100 / 170-1675m/min
Wheels	aluminium with crowned rubber tyres
Upper wheel adjustment	75mm
Table height	995 mm
Color	Blue

ELECTRICAL EQUIPMENT

Electric’s according to CE directives.

Drive motor	
Model: V2	1,5 kW; 1.500 rpm (50 Hz)
Model: V3	2,2kW; 1500 rpm (50 Hz)
Standard electrics	400 V, 50 Hz, 3 Phase

STANDARD EQUIPMENT

One set of high-speed, insert type guide-blocks for bands 3 through 13mm
One set of steel guide inserts for bands 6, 10, and 13mm
Job selector
Band speed indicator
Removable chip pan
Band tension indicator
Chip blower (requires plant air)
Post elevating hand wheel

Variable speed AC Drive (controls speeds, soft start and dynamic brake functions)

Dual range transmission

Transmission oil

Wrench for table trunnion (for Models: V3)

Wrench for saw guides (for Models: V3)

Tool kit

Instruction and parts manual (digital)

One Bimetal saw band

Band door interlocks

Europa 2013 Vertical Bandsaws - Doall produced machines.



Europa 2013-v Vertical Bandsaw range

Other options available:

[Europa 3613-V3 Vertical Bandsaw]