

Machine Specification

| | |
|-------------------------------------------------------------------------|------------------------------|
| Spindle | MKII |
| Drilling Depth (mm) | 100 |
| Tapping performance (depending on pitch) | M14 |
| Spindle Speeds infinitely variable (1/min) | 40 - 4,000 |
| Speed indicator | Digital |
| Drilling depth indicator | Digital |
| Drilling depth stop | Quickly adjustable stop ring |
| Feed rate (mm/revolution) | Manual |
| Table height adjustment | With rack |
| Three-phase motor - frequency - controlled, mains connection 400 V (kW) | 1.5 |
| Continuous/normal drilling capacity (mm) | 20/23 (in E335/ST60) |
| Projection (mm) | 240 |
| Column diameter (mm) | 82 |
| Usable work surface (W x L) (mm) | 340 x 280 |
| Distance spindle/working surface (mm) | 160- 880 |
| T-Slot size (arm), Distance (mm), Dimension width (mm) | Number 2, 125, 13/26 |
| Machine dimension without packaging (mm) | 355 x 705 x 1.825 |
| Machine Dimension with packaging (mm) | 572 x 936 x 2.142 |
| Weight (Kg) | 195 |

SUPPLIED WITH

Threading device
Control panel with OLED display
Robust, high-quality drill head hood with ergonomically inclined front
LED lighting
Quickly adjustable and ergonomic drilling depth stop
Infinitely variable speed control via central rotary knob
EMERGENCY STOP push button
Thermal overload protection
Spindle stop
Drill protection with electric Head
Connection Cable with CEE plug
3-year warranty for single-shift operation