

**Machine Specification**

Spindle	MKII
Drilling Depth (mm)	60
Tapping performance (depending on pitch)	Max. M10
Spindle Speeds infinitely variable (1/min)	40 - 3,000
Speed indicator	Digital
Drilling depth indicator	Digital
Drilling depth stop	Stop ring (form fit)
Feed rate (mm/revolution)	Manual
Table height adjustment	With rack
Three-phase motor - frequency - controlled, mains connection 230 V (kW)	0.54
Continuous/normal drilling capacity (mm)	13/15 (in E335/ST60)
Projection (mm)	180
Column diameter (mm)	70
Usable work surface (W x L) (mm)	300 x 250
Distance spindle/working surface (mm)	85 - 370 (table), 420 (feet)
T-Slot size (arm), Distance (mm), Dimension width (mm)	Cross grooves, number 2, 14/26
Machine dimension without packaging (mm)	400 x 520 x 850
Machine Dimension with packaging (mm)	452 x 700 x 1,130
Weight (Kg)	62

**SUPPLIED WITH**

Threading device  
Control panel with OLED display  
Robust, high-quality drill head hood with ergonomically inclined front  
LED lighting  
Quickly adjustable and ergonomic drilling depth stop  
Infinitely variable speed control via central rotary knob  
EMERGENCY STOP push button  
Thermal overload protection  
Spindle stop  
Drill protection with electric Head  
Connection Cable with Schuko plug  
3-year warranty for single-shift operation  
The drilling machine is equipped with a frequency converter and complies with the DIN EN 55011:2016 + A1 : 2017 standard