

Machine Specification

Spindle	B16
Drilling Depth (mm)	50
Spindle Speeds infinitely variable (1/min)	250 - 3,000
Speed indicator	Digital
Drilling depth indicator	Digital
Drilling depth stop	Quickly adjustable stop ring
Feed rate (mm/revolution)	Manual
Drill head height adjustment	Manual
Motor alternating current 230 V (kW)	0.45
Continuous/normal drilling capacity (mm)	12 (in E335/ST60)
Aluminium Ø (mm)	20
Softwood Ø (mm)	40
Projection (mm)	180
Column diameter (mm)	50
Usable work surface (W x L) (mm)	300 x 200
Distance spindle/working surface (mm)	105 - 245
T-Slot size (arm), Distance (mm), Dimension width (mm)	Number 2, 100, 12/20
Machine dimension without packaging (mm)	400 x 248 x 460
Machine Dimension with packaging (mm)	430 x 680 x 810
Weight (Kg)	30

SUPPLIED WITH

Robust, high-quality and inclined rotating hood for easy reading of the speed

LED lighting

Quickly adjustable and ergonomic drilling depth stop

Infinitely variable speed control via central rotary knob

EMERGENCY STOP push button

Thermal overload protection

Under voltage release

Drill protection with electric Hedge

Connection cable with Schuko plug (1.2m)

3- Year warranty for single-shift operation