

Machine Specification

Spindle	B12
Tapping Performance (depending on pitch)	M5
Drilling Depth	60
Spindle Speeds Infinity variable	100 - 10.000
Speed Indicator	Digital
Drilling depth indicator	Digital
Drilling depth stop	Quickly adjustable stop ring
Feed Rate (mm/revolution)	Manual
Drill head height adjustment	Manual
Motor alternating current 230 V (kW)	0.54
Continuous / normal drilling capacity (mm)	6/8 (in E335/ST60)
Projection (mm)	220
Column diameter (mm)	70
Usable work surface (W x L) (mm)	300 x 250
Distance spindle/working surface (mm)	104 - 315
T-Slot size (arm), distance (mm), dimension width (mm)	Cross grooves, number 2, 14/26
Machine dimension without packaging (mm)	320 x 520 x 820
Machine Dimension with packaging (mm)	452 x 700 x 1,130
Weight (Kg)	44

SUPPLIED WITH**Threading device****Control panel, with OLED display**

Robust, high-quality drill head hood with ergonomically inclined front
LED lighting
Quickly adjustable and more ergonomic
Drilling depth stop
Infinity variable speed control via control central rotary knob
EMERGENCY STOP push button
Thermal overload protection
Spindle stop
|Drill protection with electric hedge
Connection cable with Schuko plug
3-Year warranty for single-shift operation