

## Haco Combi 220/6

**Specification**

Capacity Mild Steel (450N/mm <sup>2</sup> ) at 30°	4mm
Capacity Mild Steel (450N/mm <sup>2</sup> ) at 60°	6mm
Blade Length	220mm
Cutting angle	30 - 140° Deg
Strokes per minute	40
Motor power	4.0kW
Table dimensions	940 x 1020mm
Working height	930
Rear station capacity	200kN
Overall dimensions	1100 x 1200 x 1400mm
Weight	1000kg

## Haco Combi 220/6

**Characteristics**

Modern design  
Sturdy mono-block construction  
Highest precision  
Hydraulic system powered by 1 cylinder  
Accurate and long guiding system  
Automatic blade-gap adjustment as a function of sheet thickness  
Flexibility by cutting different angles and materials  
Blades for stainless steel cutting  
Fast and precise cutting action

**Standard Equipment**

2 positioning squares with protractor scale, adjustable 0-90°, fixing holes every 15°  
Hydraulic Angle Notching Machine with a variable angle of 30-140°  
2 mechanical sheet hold downs  
Automatic blade gap adjustment

## Haco Combi 220/6 Variable Angle Hydraulic Corner Notcher

Mechanical vertical stroke adjuster with readout

Set of fitted 60° negative blades to cut Stainless Steel

Extra set of 30° positive blades to cut Stainless Steel

Remote Foot Pedal Control

Transparent hand-safety guards

Backstops

Internal depth stop

Large double working table, with double dovetail slots and scales

Haco Combi 220/6