

The **PRESSMASTER** is a Top-Level Synchro Pressbrake with increased daylight opening, stroke & gap featuring excellent bending angle precision. It is a more-axes CNCpressbrake with electronically controlled beam parallelism and depth-stop setting.

The combination of HACO's 2D/3D-graphic CNC control with automatic generation of the bending program, our backgauge system and the increased daylight opening makes the PRESSMASTER the most versatile press brake on the market.

- 2D/3D Graphic Controls with automatic bending sequence calculation
- Automatic generation of the bending program and Auto Tooling
- First-rate consistent angle accuracy by means of table crowning
- · Increased daylight opening, stroke and gap
- Fast X-R-Z1/Z2 Backgauge System
- Compatible with European Standard (ES) and New Standard (NS) tooling systems
- Capacity from 750 up to 2500kN, Bending Length from 2000 up to 4300mm

## Haco is launching a totally new concept for press brake controllers:

SyncView, an innovative dynamic display located on the beam that moves horizontally to the correct bending location.

## **Standard Equipment**

- FastBEND-2D Premium Graphic Control with 15" Touch Screen
- Increased daylight opening (up to 620 mm and 2500 kN models)
- Fast X-R-Z1/Z2 Backgauge
- Fast Approach Speed 200 mm/s (models up to 2000kN)
- Fast Return Speed 170 mm/s (models up to 2000kN)
- Stroke X-axis = 800mm, speed = 1000mm/s (models up to 4m and 2500kN)
- Stroke R-axis = 130mm (models up to 4m and 2500kN)
- Z1-Z2 axis, speed = 1000mm/s (models up to 4m and 2500kN)
- Manual Adjustable Crowning Table for European Standard tooling
- 2 Movable sheet supports
- European Standard toptooling with Quick Manual Clamping arrangement



