

Specification

PFG-CL3060AH & PFG-DL3060AH

Table size	300 x 600mm
Max. Grinding surface	300 x 600mm
Max. distance centre of spindle to table	500mm (Option: 600mm)
Table speed	5 ~ 25m/min
Table guideway	V & Flat way
Auto. Cross feed increment approx.	0.5mm ~ 20mm
Rapid power cross feed approx.	1100mm/min (60Hz) 900mm/min (50Hz)
Cross feed on hand wheel	1 rev 5mm
1	0.02mm
Rapid power head elevation	550mm/min (60Hz) 450mm/min (50Hz)
Vertical feed with MPG	1 rev 2mm
1	0.01mm (stand) / 0.005mm (with AD5)
Auto down feed (Option)	0.001mm ~ 0.999mm/time
Wheel speed 60Hz/50Hz	1750rpm (60Hz) 1450rpm (50Hz)
Wheel dimensions	355 x 38 x 127mm
Spindle motor	5HP
Hydraulic pump motor	1HP
Auto. Cross feed motor	1/5HP
Rapid head elevation motor	1/5HP (Optional)

Standard Equipment

Grinding wheel and wheel flange
Flange extractor
Wheel balancing arbor and base
Wheel dresser with diamond
Levelling screws and plates
Tool box and tools
Working light

Perfect PFG-CL3060 & DL3060 AH Series Saddle Type Surface Grinders

Manual