

RJH Chamois CH series of double ended polishing machines.

High quality, reliable and extremely safe polisher designed for general polishing and finishing tasks in a D&T environment. Bench, pedestal and dust extraction mounted models are available, with single or three phase electrics, with or without a braking system.

## SPECIFICATION

### DUST EXTRACTION

Weight	<b>CH2001TE 3 phase, 1500rpm</b> 93 Kg
Mop Drive Motor	<b>CH2001SE 1 phase, 1500rpm</b> 3 phase = 1.25 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm
Dust Extractor Motor	0.55 Kw

Weight	<b>CH2003TE 3 phase, 3000rpm</b> 87 Kg
Mop Drive Motor	<b>CH2003SE 1 phase, 3000rpm</b> 3 phase = 0.85 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm
Dust Extractor Motor	0.55 Kw

### PEDESTAL MODELS

Weight	<b>CH2001TP 3 phase, 1500rpm</b> 64 Kg
Mop Drive Motor	<b>CH2001SP 1 phase, 1500rpm</b> 3 phase = 1.25 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm

Weight	<b>CH2003TP 3 phase, 3000rpm</b> 59 Kg
Mop Drive Motor	<b>CH2003SP 1 phase, 3000rpm</b> 3 phase = 0.85 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm

### BENCH MODELS

Weight	<b>CH2001T 3 phase, 1500rpm</b> 40 Kg
Mop Drive Motor	<b>CH2001S 1 phase, 1500rpm</b> 3 phase = 1.25 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm

Weight	<b>CH2003T 3 phase, 3000rpm</b> 35 Kg
Mop Drive Motor	<b>CH2003S 1 phase, 3000rpm</b> 3 phase = 0.85 Kw, 1 phase = 0.70 Kw
Electrical Supply	3 phase = 400/3/50, 1 phase = 230/1/50
Maximum Mop Size	200mm x 25mm

## KEY FEATURES

Integral dust extractor with a tray collector for easier and cleaner waste handling  
Taper adaptors suitable for use with polishing mops, finishing wheels or wire brushes up to 200 x 25mm  
Supplied with two 200 x 25mm - one stitched and one loose leaf calico

## SAFETY FEATURES

No-volt overload push-button starter

- 110 volt control circuit
- Dust extraction indicator light which lights up when the filter requires servicing
- Motor thermal overload protection
- Fire retardant terylene needlefelt dustbag
- Heavy duty adjustable polycarbonate eye shields
- Large adjustable mop guards with safe edging and 3" (approx. 76mm) extraction spigots
- Excellent workpiece access
- Protective sleeves on taper nose on both sides of the polishing mop

### **OPTIONAL REFINEMENTS**

- Flexible halogen floodlight with transformer
- Lockable triple pole isolator
- Single phase unit
- Parallel adaptors
- Lockable "E" stop

## RJH Chamois CH Series Double Ended Polishers

