

Specification**GR 2003TE**

Weight	79kg
Wheel drive motor	0.85kW
Electrical supply	400/3/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Dust extraction motor	0.55kW
Grinding wheel size	200mm x 25mm x 20mm

GR 2003SE

Weight	79kg
Wheel drive motor	0.70kW
Electrical supply	230/1/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Dust extraction motor	0.55kW
Grinding wheel size	200mm x 25mm x 20mm

GR 2003TP

Weight	50kg
Wheel drive motor	0.85kW
Electrical supply	400/3/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Grinding wheel size	200mm x 25mm x 20mm

GR 2003SP

Weight	50kg
Wheel drive motor	0.70kW
Electrical supply	230/1/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Grinding wheel size	200mm x 25mm x 20mm

GR 2003T

Weight	26kg
--------	------

DUST EXTRACTION**PEDESTAL****BENCH**

Wheel drive motor	0.85kW
Electrical supply	400/3/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Grinding wheel size	200mm x 25mm x 20mm

GR 2003S

Weight	26kg
Wheel drive motor	0.70kW
Electrical supply	230/1/50
Wheel speed @ 50 Hz	2880
Wheel speed @ 60 Hz	3450
Grinding wheel size	200mm x 25mm x 20mm

Key Features

Bench, pedestal or dust extraction mounted
Adjustable, non-tip cast-iron work rests
Spark arrestors
Heavy duty adjustable polycarbonate eye shields
Grinding wheels perfectly balanced for minimum noise and vibration
Supplied with two 200 x 25x 20mm grinding wheels

Key Safety Features

No-volt overload push-button starter
Motor thermal overload protection
110 volt control circuit (extraction versions only)
Full wheel guarding
Foot stop (pedestal versions only)
Dust extractor features:
0.55kw motor
Tray collector for easier and cleaner waste handling
Indicator light which lights up when the filter requires servicing
Fire retardant terylene needlefelt dustbag

Remote knee stopbar