

Machine Specifications	600RT6
Maximum distance between centres	600mm
Maximum grinding length	600mm
Height of centres over table	160mm
Swing over table	315mm
	1000RT6
Maximum distance between centres	1000mm
Maximum grinding length	1000mm
Height of centres over table	160mm
Swing over table	315mm

Machine is equipped with:

PRO-FACE touch screen control panel
Wheel head and table automatic electronic feed controlled by motor brushless
Incremental optic rule for micro positioning of wheel head
Table manual swivelling system for taper grinding with dial gauge
Re-circulating ball screw with preloaded nut for wheel head and table movement
Anti-friction material on wheel head guides
Electric installation, in separate cabinet
Pneumatic unit
Centralized lubrication

Standard Equipment

Coolant equipment complete with pump, tank, pipes and nozzle
Straight wheel dressing unit (diamond optional) mounted on tailstock
Grinding wheel diam. mm. 450, thickness mm. 50, hole mm. 127
Grinding wheel flange
Wheel balancing arbor
Wheel extractor
Additional pulley for wheel motor
2 hard metal tipped centres
Set of levelling screws and plates

2 cloth bellows for table guide protection

Sliding doors on base

Set of service spanners & Set of hexagonal spanners

5 Kg. oil for wheel spindle lubrication & 5 Kg. oil for guide lubricating

Instructions manual