

Europa Trading Estate Fraser Rd, Erith, Kent England

Tel: 01-304 8411

Telex: 896221 RK INTOOLS

SOLE U.K. DISTRIBUTORS FOR ARKADIA MININI SURFACE GRINDERS: ARKADIA PUNCHING AND NOTCHING MACHINES: INDUMA MILLING MACHINES: INDUMA SECMU A-ZERO: ARKADIA SURFACE GRINDER ARKADIA MANLOVE CENTRIFUGAL OIL SEPARATORS AGENTS FOR ALL BRITISH AND CONTINENTAL MANUFACTURERS

SUMMER 1976 STOCK LIST

Gentlemen,

We are now happy to say that business seems to be consistently improving. This is confirmed by many of you whom we meet in the field and is very encouraging indeed.

This situation is also reflected in the way that many manufacturers are now offering longer deliveries on their machines. To counteract this and in order to provide a more efficient service to our customers we are now maintaining a stock level of approximately £750,000.

Continuing on this theme we have recently formed a subsidiary Company in Dublin (R.K. INTERNATIONAL MACHINE TOOLS (IRELAND) LIMITED) to cope with the ever increasing demands for machine tools and sheet metal working equipment from Eire.

We are happy to report that in the four months of the Company's existence they have exceeded all expectations and indeed are as optimistic as ourselves for the future.

Since our last Stock List was published we have been appointed sole distributor in the South East for the MECOF range of Radial Drilling Machines. MECOF are renowned for their rigidity and accuracy but at the same time are a very compact machine. We have various models in stock available for your inspection.

We would like to extend our usual cordial invitation to visitors to our showrooms and arrangements can be made for visits outside normal working hours.

All machines in our Stock List are motorised 400/440/3/50 Cycles unless otherwise stated.

Details of all machines supplied on request,

All prices quoted are exclusive of V.A.T.

INDEX

USED MACHINE TOOLS NEW MACHINE TOOLS

pages 1-2

pages 3 - 11

Directors: R. Schwarz M. R. Schwarz







CAPSTAN (continued)

HERBERT 2D

1.5/8" capacity. Speeds (8) 50-2550 rpm. Equipped with ball chuck, 3-jaw chuck, 4-way & rear toolposts, coolant, collets, large assortment of tooling, bar feed. Year of manufacture 1951

£1100.00

TOS STROJIMPORT MODEL RC.100 4" capacity. 29.3/4" swing over bed. Speeds (8) 16-900 rpm. Equipped with 4-way toolpost, 2 rear toolposts, 3-jaw chuck, tooling. Year of manufacture 1961

P.O.A.

WARD 10 COMBINATION Speeds (16) 10-290 rpm. Equipped with 3-jaw chuck, 4-way toolpost and knee tool

£ 750.00

CENTRE

COLCHESTER STUDENT

Swing 12", 24" between centres, speeds (8) 54-1200 rpm. Equipped with 3 & 4 jaw chucks, hydraulic copy unit, quick change toolpost, travelling steady, coolant and splashguard. Year of manufacture 1969

£1600.00

£1200.00

£3850.00

MILLING

BED TYPE

ARNO MODEL FA.1500 BORING/MILLING Table size 64" x 36". Speeds (16) 18-1000 rpm Spindle 50 INT. Equipped with power feeds and rapids in all directions, 2 arbors & arbor support, motorised overarm, vernier scales. Year of

manufacture 1965. Machine in excellent £13,250.00 condition

HORIZONTAL

BIRFIELD SOMUA TYPE Z3C AUTO CIRCLE Table size 63" x 14.1/2". Speeds 43-1900

rpm.

UNIVERSAL

INDUMA MODEL NL/49 Table 49.1/4" x 10". Speeds 40-1600 rpm. 40 INT Power feeds & rapids in all

directions. Equipped with coolant. Year of manufacture 1975

PRESSES

EDWARDS APEX MODEL EP

£ 65.00 Foot lever press

ESSA MODEL RB10 SHAVING PRESS

£ 750.00 10 ton capacity

£ 120.00 Hand operated

SWEENEY & BLOCKSIDGE WHEELING PRESS

SAWING

GACO CIRCULAR SAW

Capacity 10" x 4" sections, 10" x 3" solids. Equipped with coolant. Year £ 950.00 of manufacture 1973

SHAPING

ROYAL

Stroke 10" Speeds 43-118 spm. Year of manufacture circa 1962. Equipped £ 395.00 with swivel table

SHEET METAL

NIBBLING

PELS_MODEL AS5 4 swg 42" throat

£ 425.00

SHEARING

FERROUS MODEL GB14 HAND LEVER SHEAR Capacity 14 swg mild steel, mounted

£ 90.00 on stand

WELDING

B.O.C. QUASI ARC TYPE CPU.300/Q Mounted on wheels. Output 21.5 kVA continuous 30 kVA max. £ 225.00

MISCELLANEOUS

B.I.C.C. CAPACITOR 55 kVA.

£ 140.00

DAVENSET MODEL D8013 BATTERY £ 100.00 CHARGER

Prices given are generally basic prices, but detailed quotations and literature will be supplied on request.

Items marked 'S' are available from stock at time of printing and provided the machine

is not sold, the price will be honoured despite any manufacturer's price increase which

Items marked 'SD' are those on order for stock or available for short delivery. These prices are subject to manufacturer's price variations

BORING	PRICE EACH	BEI	NCH & PEDESTAL (continued)	PRICE EACH
HORIZONTAL Agents for GATE, JUARISTI, UNION, PLAUERT, AYCE and AJAX JIG		SD	ARBOGA MODEL GM.2512 PILLAR 1.1/4" capacity, all geared head, power feed to quill, equipped with square table	£ 874.00
Agents for B.C.A., GATE ELGA, GATE OMEGA and NEWALL		SD	ARBOGA MODEL G.2508 PILLAR 1.1/4" capacity, all geared head, spindle speeds (8) 100-2900 rpm	£ 548.00
VERTICAL		00	AB200 A 140 D F 1 F 200 D 11 1 1 D	
Agents for SKODA and HARTLE STEDA	ALL	SD	ARBOGA MODEL E.830 PILLAR 1.1/4" capacity, all geared head,	
COMPRESSORS			power feed to quill. Equipped with rectangular table, speeds (8) 80-	
SD ATLAS COPCO MODEL FE2EA31			890 rpm	£1056.00
1.6 cfm at 100 psi	£ 240.00	SD	ASTRA TYPE IM/103 BENCH	
SD ATLAS COPCO MODEL FE4EA31 3.3 cfm at 100 psi	£ 280.00	30	1/8" capacity, speeds 3000-18,000 rpm. Table size 7.7/8" x 7.7/8". Ed	Juipped
SD ATLAS COPCO MODEL FE5EA32			with magnifying glass, spotlight, switch, chuck and chuck guard	£ 470.00
4.6 cfm at 100 psi	£ 365.00		switch, chuck and chuck guard	£ 470.00
CD ATLAC CORCO MODEL MEDAGO		SD	ASTRA TYPE 0/6 SENSITIVE BENC	
SD ATLAS COPCO MODEL KE2A32 9.5 cfm at 100 psi	£ 465.00		1/4" capacity, speeds 1500-8000 rp Table size 7" x 8 1/4". Equipped with spotlight, chuck and chuck	om.
S ATLAS COPCO MODEL KE6B44			guard.	£ 237.00
29.4 cfm at 100 psi	f 840.00			
SD ATLAS COPCO MODEL KE6B24			MEDDINGS DRILTRU 1/2" Capacity	:-
35 cfm at 100 psi	£ 810.00	SD	BENCH, 3 phase	£ 136.00
S ATLAS CODOS MODEL METADA		SD	BENCH, 1 phase	£ 142.00
S ATLAS COPCO MODEL KE4B24 18.6 cfm at 100 psi	£ 595.00	S	PEDESTAL, 3 phase	£ 144.00
	1 333.00	S	PEDESTAL, 1 phase	£ 150.00
SD ATLAS COPCO MODEL KE4B44 18.6 cfm at 100 psi	£ 625.00	SD	MEDDINGS MODEL A10 ARTICULA HEAD, PEDESTAL	
S BINKS BULLOWS MODEL 55ASR.2301 HYDROVANE			Capacity 3/4" Spindle speeds 80-40 rpm, 24" throat	00 £ 798.00
21.7 cfm at 100 psi	£ 820.00		MEDDINGS MODEL M2 : 5/8" Capac	ity:-
We are also agents for H.C.P. and C. & H.		SD	BENCH, 3 phase	£ 204.00
we are also agents for H.C.F. and C. & H.		SD	BENCH, 1 phase	£ 211.00
DRILLING		S	PEDESTAL, 3 phase	£ 224.00
BENCH & PEDESTAL		SD	PEDESTAL, 1 phase	£ 231.00
BENCH & FEDESTAL			MEDDINGS MODEL M4: 7/8" capaci	ty:-
SD AJAX MODEL AJ.50 PILLAR		S	BENCH, 3 phase	£ 282.00
2" capacity, all geared head, power feed		SD	BENCH, 1 phase	£ 292.00
to quill, equipped with lighting, coolant, speeds (9) 62-964 rpm	£1755.00	S	PEDESTAL, 3 phase	£ 296.00
	21700.00	SD	PEDESTAL, 1 phase	£ 306.00
SD AJAX MODEL AJ.60 PILLAR 2" capacity, all geared head, power feed, power elevation to head and table,		SD	QUALTERS & SMITH MODEL QDM. BENCH	
equipped with lighting and coolant. Speeds (9) 62-964 rpm	£3761.00		Capacity 7/8" Speeds 50-3500 rpm	£ 307.00

DRI	LLING (continued)	PRICE EACH	DRILLING (continued)	PRICE EACH	GRINDING (continued)	PRICE EACH	GRINDING (continued)	PRICE EACH
	BENCH & PEDESTAL (continued)		MULTI SPINDLE		CYLINDRICAL & UNIVERSAL ((continued)	SURFACE (continued)	
S	QUALTERS & SMITH MODEL QDM.750 BENCH		SD MEDDINGS 4 HEAD 1/2" capacity, heads mount		SD MYFORD MODEL MG12 5" swing x 12" between centres S MYFORD MODEL MG12HA		vertical traverse 16". Equippe with rapid vertical traverse, I	ong.,
SD	Capacity 3/4" QUALTERS & SMITH MODEL QDM.32 PILLAR	£ 257.00	common table SD MEDDINGS 4 HEAD 3-off 5/8" capacity heads, 1 capacity head, mounted on		5" swing x 12" between centres equipped with hydraulic table traverse with dwell control, rap advance and retraction to whee	id Ihead,	cross and vertical power feed coolant equipment and auto spark-out finish cycle, single magnetic filter, wheel balance	matic action cing unit
	Capacity 1.1/4" Speeds 70-1500 rpm. Power feed to quill, rectangular table	£ 981.00	table, complete with coolan equipment SD MEDDINGS 6 HEAD	£1284.00	auto. Wheelhead infeed and cod equipment S SZIM MODEL KU-250-03/750 UN 10" swing x 30" between centre	£3981.00 NIVERSAL	and spare grinding wheel flar SD ARKADIA MININI TYPE TH/ Working surface 32" x 20" l traverse 35", cross traverse 2	PL 8-6 Long
	We are also agents for UNION, FLOTT, TOS DENBIGH and STARTRITE MAGNETIC	o,	4-off 5/8" capacity heads, 2 capacity heads, mounted on T-slotted table SD MEDDINGS 4 HEAD		equipped with sizing attachmen coolant, balancing mandrel, stea lighting, wheel dresser stand, in	at, ady, ternal	vert. traverse 15", equipped rapid vert. traverse, long. & opower feed, coolant & auto.	with cross spark-
SD	WOLF MAGNETIC DRILL STAND & DRII COMBINATION Drill capacity 29/32" 230 volts,	LL	4-off 7/8" capacity heads, non common table complete coolant equipment		grinding attachment and quill, 3 chuck, micrometer stop, tool ca grinding wheels, hydraulic tailst splashguard, lighting	abinet,	out finish cycle, single action magnetic filter, wheel baland and spare grinding wheel flan SD ARKADIA MK.2	cing unit
SD	1 phase VERROLEC MAGNETIC DRILL	£ 413.00	FILING		SD TOŚ KAMENICEK UNIVERSAL 2UD/500	MODEL	Table size 18.1/2" x 6.1/2"	£ 970.00
	COMBINATION Drill capacity 1.1/4" 230 volts, 1 phase	£ 610.00	Agents for LIMATIC, NEW WO	ONDER,	11.1/2" swing x 20" between complete with hydraulic infeed rapid traverse of wheelhead, light	with hting	We are also agents for TOS, GA and MYFORD JOTES	TE STEFOR
	RADIAL		GRINDING		and coolant pump & fittings We are also agents for CHURCHIL	£4401.00	TOOL AND CUTTER SD ASTRA JYPE AR5E/T	
SD	ARBOGA TYPE ER.825 25" RADIAL 1" capacity, speeds (8) 100-2900 rpm	£1270.00	BAND		DOUBLE ENDED		22.1/2" between centres, eq with universal dividing head,	, twist
SD	ARBOGA TYPE RLM.3512 39" RADIAL 1.3/8" capacity, speeds 60-1645 rpm complete with box table, coolant,		S ASTRA Band size 36" x 4" 3 phase 1 phase		SD ARBOGA TYPE E.308 BENCH 8" wheels SD ARBOGA TYPE EP.308 PEDESTA	£ 157.50	drill unit, coolant and lightin S CLARKSON MARK 1 6" swing over table, 12" bet	ween
S	lighting, power elevation to arm MECOF MODEL 35C 46" RADIAL 1.1/2" capacity, speeds (12) 35-1460	£4020.00	SD VANCO FLEXIBAND 700 Band size 42" x 2" complet	e with	8" wheels SD ARBOGA TYPE EP.312 PEDESTA	£ 215.00	centres S RIPBITS MODEL H3 DRILL B Max. diameter 2"	£ 430.00 BIT £ 225.00
	rpm. Complete with coolant, box table, lighting, power elevation to	C4205 00	abrasive belt guard	£ 239.00	12" wheels SD BRITAN 4 WHEEL BENCH	£ 393.00	S RJH 'FERRET' TRIM'TOOL G Speed 4470 rpm Wheel size (
SD	MECOF MODEL 40C 59" RADIAL 1.3/4" capacity, speeds (12) 35-1460	£4385.00	We are also agents for R.J.H. CENTRELESS	405	6" wheels We are also agents for GRIMSTON	£ 110.00	S STRIGON TOOL GRINDER M TMP200-K/A Capacity 1/8" min. – 19/32	" max.
CD.	rpm. Complete with coolant, box table, lighting, power elevation to arm	£5767.00	SD GATE ESTARTA MODEL GE 2" capacity, equipped with wheel dressing unit, through	hydraulic i feed	UNION, ELLIOTT, GATE and MI INTERNAL	LFORD	work diameter admitted We are also agents for ELLIOT	£ 325.00
SD	QUALTERS & SMITH MODEL QSR.3 33" RADIAL 1.1/2" capacity, speeds 60-1750 rpm	£2865.00	grinding unit, coolant and c cycle S GATE ESTARTA MODEL GE	£8595.00	Agents for GATE RIBON SURFACE		ABWOOD and UNION TOOL POST	
SD	QUALTERS & SMITH MODEL QSR.4 45" RADIAL 1.1/2" capacity, speeds 60-1750 rpm	£3036.00	As above but without contro cycle SD GATE MODEL GPM.65M	£6275.00	SD ABWOOD TYPE 5025CP Working surface 20" x 10", pov	AVO.	SD DUPLEX TYPE D30A HEAVY EXTERNAL 1 phase	' DUTY £ 113.00
SD	TOS MODEL VR2 36" RADIAL 1" capacity, speeds 90-4500 rpm	£2458.00	1" capacity, equipped with and manual wheel dressing u		longitudinal and cross traverse a rise & fall workhead, coolant	and	LATHES	
SD	TOS MODEL VR4 49" RADIAL 4 MT spindle, speeds 45-2000 rpm, complete with box table	£4356.00	SD GATE MODEL GPM65DI 1" capacity, equipped with		equipment and magnetic chuck SD EAGLE MODEL 4W	£4227.00	AUTOMATIC CAPSTAN SD BRITAMATIC MODEL 'E' MK	1Δ
	We are also agents for AJAX, ELLIOTT,	14350.00	and hydraulic wheel dressing S GATE MODEL GPM65DI.MIA 1" capacity, equipeed with		Working surface 18" x 6". Equipped with coolant SD GATE JAKOBSEN SJ.12	£1203.00	1.1/4" capacity, sequential of Equipped with bar feed	
	GATE, MEX and RICHMOND TURRET		hydraulic wheel dressing un controlled cycle	£6845.00	Working surface 25" x 10". Equipped with coolant, rapid vertical traverse, longitudinal &		We are also agents for SMART 8 GATE WINCHESTER and SKO	
SD	ASTRA MECA 1/2" capacity, complete with floor	C107C 00	We are also agents for TOS	Table 1	cross power feed SD GATE JAKOBSEN SJ.16	£4995:00	CAPSTAN SD BRITAN MODEL 'E' MK.1A R	
	cabinet and coolant BURGMASTER MODEL OB 1/4" capacity	£1976.00 £ 890.00	SD GATE RIBON MODEL 500A (11" swing x 20" between ce	UNIVERSAL entres,	Working surface 32" x 10". Equipped with coolant, rapid vertical traverse, long. & cross		1.1/4" capacity. Speeds 56-1 Equipped with pneumatic ba power operated hydraulic lo	er feed, ngitudinal
S	BURGMASTER MODEL 1D 1/2" capacity, complete with floor cabinet and tooling	£2308.50	complete with internal grind attachment	£4995.00	power feed S ARKADIA MININI TYPE TH/PL (Working surface 24" x 20", long	g	feed unit. S MYFORD MODEL C7 5/8" capacity, equipped with	£2008,00
SD	BURGMASTER MODEL 2B 3/4" capacity, complete with coolant equipment	£7250.00	SD GATE RIBON MODEL 800A I 11" Swing x 32" between complete with internal grind	entres,	traverse 27", cross traverse 24.3	78",	chuck and coolant equipmen 33-1680 rpm	£ 998.75

£5295.00

attachment

LA	THES (continued)	PRICE EACH	LATHES (continued)	PRICE EACH					
	CAPSTAN (continued)		CENTRE (continued)		L	ATHES (continued)	NEW MACHINE TOOLS AND	SHEET METAL EQUIPMENT MILLING (continued)	DDIOE FAOU
S	TOS MODEL R5 2.08" capacity, speeds 24-1400 rpm. Power feed to turret and saddle,		SD GATE STURDITURN 7.1/2" x 40". Speeds 45 Gap. Bed. Equipped with			CENTRE (continued)	PRICE EACH	TURRET	PRICE EACH
	Equipped with coolant, bar feed and collet chuck OK We are also agents for AJAX, GATE SPRINGATE RVL, GATE RVM, GATE PR and	£6634.00	toolpost, coolant, guards S BOXFORD MODEL AUD 4.5/8" x 16" Speeds 40- Equipped with coolant	£1750.00	SC	10.82" x 79". Spindle spee Equipped with 4 way tool chuck, faceplate, fixed and	eds 10—1000. post, 3 jaw I travelling	S GATE PROFITMIL Table 48" x 10". Spindle speeds 57–2: rpm. Long power feed S INDUMA MODEL 1S	275 £2550.00
	SMART & BROWN CENTRE		SD BOXFORD MODEL AUD 4.5/8" x 22" Speeds 40- Equipped with coolant	1400 rpm. £ 923.00		steadies, coolant and lighti Agents for OKUMA, CRO	WTHORN, BUTLER,	Table 42" x 9". Speeds 65–2200 rpm. 2 HP Motor, long. power feed, coolant,	
SD			SD BOXFORD MODEL VSL-L 5" x 20" Spindle speed in 50-2000 rpm. Equipped v	OO SERIES 500 nf. variable	МІ	ENCOMAT, MAXIMAT, S STANLEY AND BINNS & LLING		30 INT., 13½" cross traverse S INDUMA MODEL 1S/44 Table 42" x 9". Speeds 65–2200 rpm. Power feeds and rapids in all directions	£2431.00
	steady, 5 posn. longitudinal bedstop, rapid power traverse to saddle and cross slide, coolant, 4-way toolpost and lighting	£5120.00	S HARRISON 11" SWING 5.1/2" x 25" Spindle spe rpm		s	BED TYPE INDUMA SECMU MODEL Fixed Bed. Table work are:	a 16" × 60".	30 INT. Equipped with coolant S INDUMA MODEL 3S/M Table 55.1/8" x 11". Speeds inf. variab	£3626.00
	COLCHESTER BANTAM Spindle speeds 36-800 rpm. Equipped with 3-jaw chuck, coolant and splashguard:—	13120.00	HARRISON M.300 Spindle speeds 45-2000 r SD 6" x 25" SD 6" x 40"	pm. Gap. Bed. £1452.00 £1564.00		Speeds (18) 25–940 rpm. Inf. variable feeds and rapid and long movements of tab movement of head. Spindle	d feeds in cross le and vertical	60-4000 rpm. 3 HP Motor, spindle tap 40 INT. Equipped with coolant SD INDUMA MODEL 3S/A As Model 3S/M but also equipped with	£4718.00
S SD	5" x 20" 5" x 30"	£1261.00 £1325.00	S HARRISON 15" SWING 7.1/2" x 50" Spindle sper rpm. Gap Bed. Equipped		t s	COPY INDUMA MODEL FC/6		variable longitudinal and cross feed and powered vertical positioning of table	
S	COLCHESTER CHIPMASTER 5" x 20". Spindle speeds inf. variable 35-3000 rpm. Equipped with 3-jaw chuck, coolant, splashguard	£1739.00	chuck and coolant HARRISON M.400 Spindle speeds 40-2000 r	£2356.00	6	Table 71" x 20". Speeds 50 3-Axis copying	02500 rpm. £18872.00	S INDUMA MODEL 5S/60 Table 67" x 14.3/16". Speeds (16) 50- rpm. Power feeds and rapids in all direc	-2500
	COLCHESTER STUDENT 1800 Spindle speeds 22-1800 rpm. Gap Bed. Equipped with 3-jaw chuck, coolant and splashguard:—	1739.00	SD 8.1/4" x 40" SD 8.1/4" x 60" HARRISON M.450 : 17" SW Spindle speeds (16) 22-17	£2895.00 £3020.00 VING	SD	ASTRA MODEL L2 Table 13" x 4.1/8". Speeds No.2 MT	500—2000 rpm. £ 308.00	40 INT. Equipped with coolant S INDUMA MODEL 5S/70 Table 74%" x 15%". Speeds (16) 50–29 rpm. Power feeds and rapids in all direct	£8997.00
S SD	6.1/2" x 25" 6.1/2" x 40" COLCHESTER MASTER 2500	£1732.00 £1769.00	Gap Bed SD 8.1/2" x 40" SD 8.1/2" x 60" SD 8.1/2" x 80"	£4455.00 £4520.00 £4565.00	SD	ASTRA MODEL L4 Table 16" x 5". Speeds 420 No.2 MT		40 INT. Equipped with coolant Agents for AJAX and TOS UNIVERSAL	£9594.00
SD S	Spindle speeds 30-2500 rpm. Gap Bed. Equipped with 3-jaw chuck, coolant, splashguard:— 6.1/2" x 25" 6.1/2" x 40"	£1942.00	SD 8.1/2" x 100" HARRISON M.540 : 21" SW Spindle speeds (16) 19-15 Gap Bed.		S	C.M.E. MODEL F.900 RH Automatic Long. Cycle. Ta x 6.11/16". Speeds (9) 50-	-1280 rpm.	SD INDUMA MODEL UM/44 Table 42" x 9.1/16". Speeds (12) 40–1 Power and rapid feeds in all directions.	600 rpm.
3	COLCHESTER TRIUMPH 2000 Spindle speeds 25-2000 rpm. Gap Bed. Equipped with 3-jaw chuck, coolant,	£1979.00	SD 10.1/2" x 40" SD 10.1/2" x 60" SD 10.1/2" x 80" SD 10.1/2" x 100"	£5285.00 £5335.00 £5385.00 £5750.00	S	30 INT INDUMA MODEL NLP/56 Table 67" x 11.13/16". Spe 50 INT. Equipped with coo	eeds 30–1500 rpm	Equipped with coolant S INDUMA MODEL NL/49 Table 49%" x 10". Speeds 40–1600 rpr	£4385.00
SD S	splashguard:— 7.1/2" x 30" 7.1/2" x 50" COLCHESTER TRIUMPH 2000 TR	£2399.00 £2451.00	SD 10.1/2" x 120" SD MYFORD MODEL ML7 7" swing x 20"	£6330.00 £ 292.00	§ s	feeds and rapids in all direct INDUMA MODEL NLP/63 Table 75" x 16". Speeds 30	£8178.00 0—1500 rpm.	40 INT. Power feeds and rapids in all directions. Equipped with coolant S INDUMA MODEL NL/51	£4895.00
	Spindle speeds 25-2000 rpm. Straight Bed Toolroom Lathe. Equipped with 4-way toolpost, 3-jaw chuck, lighting, coolant, splashguard:—		SD MYFORD MODEL SUPER 7 7" swing x 19" SD MYFORD MODEL 280	£ 515.00) SD	50INT. Power feeds and rap directions. Equipped with c INDUMA MODEL NLP/87	oolant £8667.00	Table 59" x 11". Speeds 30–1500 rpm. 40 INT. Power feeds and rapids in all did Equipped with coolant SD INDUMA MODEL NL/56	
SD SD	7.1/2" x 30" 7.1/2" x 50" COLCHESTER MASCOT 1600	£3087.00 £3136.00	11" Swing SD TOS MODEL SN.40B/1000 7.87" x 39.1/2" Spindle s	£ P.O.A.		Table 94½" x 17.15/16". S 50 INT. Power feeds and ra directions. Equipped with c	pids in all	Table 63" x 11.13/16". Speeds 30—150 50 INT. Power feeds and rapids in all directions.	ections.
	Spindle speeds 20-1600 rpm. Gap Bed. Equipped with 3-jaw chuck, coolant, splashguard:—		22.4-2000 rpm. Equipped 4-way toolpost, 3-jaw chu plate, fixed & travelling st coolant and lighting	ck, face-	SD	SENIOR MODEL M1 Table 28" x 6%". Speeds 50 30 INT. 1 HP. Equipped with		SD INDUMA MODEL NL/63 Table 75" x 13%". Speeds 30–1500 rpn 50 INT. Power feeds and rapids in all dir	
SD SD SD SD	8.1/2" x 40" 8.1/2" x 60" 8.1/2" x 80" 8.1/2" x 100"	£3412.00 £3472.00 £3532.00 £3892.00	SD TOS MODEL SN.40B/1500 7.87" x 59" Spindle speed 2000 rpm Equipped with 3-way chuck, faceplate, fix	is 22.4- 4-way toolpost.		Agents for AJAX, GATE CI HARRISON, ELLIOTT, and DIE SINKING PANTOGRA	d TOS	Equipped with coolant S INDUMA MODEL NL/87 Table 95" x 17". Speeds 30–1500 rpm.	£9209.00
	COLCHESTER MASTIFF 1400 Spindle speeds 18-1400 rpm. Gap Bed. Equipped with 3-jaw chuck, coolant, splashguard:—		travelling steadies, coolant SD TOS MODEL SN.50B/1000 9.84" x 39.1/2" Spindle si	: & lighting £3017.00	S	STRIGON MODEL MP200 3 dim. universal pantograph engraving machine. Reduction	milling and	50 INT. Power feeds and rapids in all dir Equipped with coolant S INDUMA MODEL NL/87 with MOTOR	£14154.00
SD SD SD	10.1/2" × 40" 10.1/2" × 60" 10.1/2" × 80"	£4204.00 £4274.00 £4344.00	 2000 rpm Equipped wit lighting, 3-jaw chuck, face and travelling steadies and toolpost 	h coolant plate, fixed		1:10, max. 1:5. Work table Template table 1.3/8" x 175 with standard tools, lighting	8" x 12½". ¼". Equipped	OVERARM As above but equipped with coolant, aut	omatic
SD S	10.1/2" x 100" 10.1/2" x 120"	£4874.00 £5528.00	to those	13200.00		grinding machine	£2020.00		

Table 59" x 11". Speeds 30—1500 rpm. 40 INT Main Horizontal spindle. 35D NORTON FLY NO: 3	MILLING (continued)	PRICE EACH	PRE	SSES (continued)	PRICE EAC
Lubrication, O.P.L. optics on 2 axes and rear control Agents for GIEWONT, TOS, AJAX, HARRISON and ELLIOTT UNIVERSAL TURRET INDUMA MODEL NLS1-T3S Table 59" x 11", Speeds 30—1500 rpm. 40 INT Main Horizontal spindle, 3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant VERTICAL D ARBOGA MODEL U.2508 Table 22" x 10", Speeds 100—2900 rpm (100 MODIAM MODEL VMC) Table 49%" x 10", Speeds 100—2900 rpm (100 MODIAM MODEL VMC) Table 49%" x 10", Speeds 100—2900 rpm (100 MODIAM MODEL VMC) Table 49%" x 10", Speeds 100—2900 rpm (100 MODIAM MODEL VMC) Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 49%" x 10", Speeds 100—2900 rpm (100 MODIAM MODEL VMC) Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 49%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA MODEL VMR0 Table 69%" x 17% rower feeds and rapids in all directions. Equipped with coolant UNDIMA	hydraulic backlash eliminator, automatic		S	ARKADIA PUNCHMATIC MODEL 40/30	
Agents for GIEWONT, TOS, AJAX, HARRISON and ELLIOTT UNIVERSAL TURRET INDUMA MODEL NLS1-73S Table 59" x 11", Speeds 30—1500 pm. 40 INT Main Horizontal spindle. 3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant VERTICAL D ARBOGA MODEL U.508 Table 29" x 10", Speeds 100—2900 pm INDUMA MODEL VM/9 INDUMA MODEL VM/9 Table 39" x 10" x 1				HOLE PUNCHING & NOTCHING	
Agents for GIEWONT, TOS, AJAX, HARRISON and ELLIOTT UNIVERSAL TURRET INDUMA MODEL N.E1-T3S Table 89" x 11" Speeds 30–1500 rpm. 40 INT Main Horizontal spindle. 3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with colorant with colorant with colorant and received the colorant in John Mark 1997 (200 pp. 1900 pp				MACHINE	
HARRISON and ELLIOTT UNIVERSAL TURRET INDUMA MODEL NL51-T3S Table 59" x 11", Speeds 30—1500 rpm. 40 INT Main Horizontal spindle. 3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant E8912.00 D ARBOGA MODEL U.2508 Table 29" x 10" 40 INT. Spindle speeds 40—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant E992.00 INDUMA MODEL WM/90 Table 59" x 11" 50 INT. Spindle speeds 40—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant E992.00 INDUMA MODEL WM/90 Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Equipped with coolant E8912.00 Agents for CRESSEX, MARLCO and ToS SAWING BAND Agents for CRESSEX, MARLCO and ToS SAWING BAND AGENTEM MODEL RE.80 Open front mechanical 60 ton capacity, adjustable stroke, of Japon power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant CAPACADIA RESSEX D CHURCHILL MODEL 37UC Double sided hydraulic 60 ton capacity, adjustable stroke, of Japon power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with recive feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapid	A C OFFICALT TOO A LAY	210100.00		Capacity 40 ton, throat depth 30". Max.	
UNIVERSAL TURRET INDUMA MODEL LIST-TS Table 59" x 11". Speeds 30–1500 rpm. 40 INT Main Horizontal spindle. 3 HP variable speed turset head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant VERTICAL ARBOGA MODEL U.2508 Table 22" x 10". Speeds 100–2900 rpm INDUMA MODEL W.490 Table 49%" x 10" 40 INT. Spindle speeds 40–1800 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL W.490 Table 49%" x 10" 40 INT. Spindle speeds 30–1500 rpm. Equipped with coolant UNDUMA MODEL W.490 Table 59" x 11" 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant UNDUMA MODEL W.490 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 178% Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 178% Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL W.490 Table 86%" x 178% Down Feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DindumA MODEL W.490 Table 86% Table 86% Table 86% Down Feeds 86% Down		1		size of sheet without relocating 60" x 30".	
INDUMA MODEL NL51-T3S Table 59" x 11", Speeds 30—1500 rpm. 40 INT Main Horizontal spindle. 3HV variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant 50 INDUMA MODEL VM/90 E500.0 INDUMA MODEL VM/90 E6591.00 INDUMA MODEL VM/90 Indumental E6291.00 Indumental E6291.	HARRISON and ELLIOTT	\sim		Equipped with recirculating bearings on	
INDUMA MODEL NL51-T3S Table 59" x 11". Speeds 30—1500 rpm. 40 INT Main Horizontal spindle. 3HP variable speed turset head 40 (INT and vertical head mounted on swivelling overarm, Power feeds and rapids in all directions. Equipped with coolant VERTICAL D ARBOGA MODEL U.2508 Table 52" x 10" Speeds 100—2900 rpm INDUMA MODEL WM/49 Table 49x" x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant Graph Speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all dire	LINIVERSAL TURRET			X & Y traverses and repeat punching	
Table 59" x 11". Speeds 30—1500 rpm. 40 INT Main horizontal spindle. 3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant 50 NoRTON FLY NO: 4 Deep Throat 51 P250.0 NORTON FLY NO: 5 Deep Throat 52 P250.0 NORTON FLY NO: 6 P250.0 NORTON F				facility	£9985.00
rpm. 40 INT Main Horizontal spindle. 3RP Variable speed turrer head 40 INT and vertical head mounted on swivelling overarm, Power feeds and rapids in all directions. Equipped with coolant 50 NORTON FLY NO: 5 Deep Throat £ 250.0 NORTO			SD	NORTON FLY NO: 2	£ 113.00
3HP variable speed turret head 40 INT and vertical head mounted on swivelling overarm. Power feeds and rapids in all directions. Equipped with coolant D ARBOGA MODEL U.2508 Table 22" x 10". Speeds 100–2900 rpm INDUMA MODEL VM/80 Table 49%" x 10" 40 INT. Spindle speeds 40–1800 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL VM/80 Table 59" x 11" 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity, adjustable stroke no fiaplock guard) ARKADIA PUNCHMATIC MODEL 20/20 ARKADIA PUNCHMATIC MODEL 20/20 ARKADIA PUNCHING Time feeds and rapids to adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and rapids to apparity adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and rapids to apparity adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and rapids to apparity adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and rapids to apparity adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and rapids to apparity adjustable stroke no fiaplock guard) ARKADIA PUNCHING Time feeds and feeds for form. ARKADIA PUNCHING Time feeds for			SD	NORTON FLY NO: 3	£ 134.00
40 INT and vertical head mounted on swivelling overarm, Power feeds and rapids in all directions, Equipped with coolant VERTICAL D. ARBOGA MODEL U.2508 Table 92" x 10" Speeds 100—2900 rpm INDUMA MODEL VM/49 Table 49%" x 10" speeds 100—2900 rpm INDUMA MODEL VW/49 Table 49%" x 10" speeds 100—2900 rpm INDUMA MODEL VW/49 Table 49%" x 10" speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant InDUMA MODEL VW/60 Table 50" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentations. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentation and Indumentation. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation and Indumentation. Spindle speeds 30—1500 rpm. Equipped with coolant Indumentation Indu			SD		£ 178.00
swivelling overarm. Power feeds and rapids in all directions. Spingle with coolant Description of the property of the propert			SD	NORTON FLY NO: 4 Deep Throat	£ 220.00
rapids in all directions. Equipped with coolant SABOR ADDEL U.2508 Table 22" x 10". Speeds 100—2900 rpm S1254.00 INDUMA MODEL V.M/49 Table 49%* x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL V.M/70 Table 67" x 11" 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/70 Table 76" x 11" 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/70 Table 86%* x 17" 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/70 Table 86%* x 17" x 15". Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/90 Table 86%* x 17%*. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES DI CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity, adjustable stroke (pot mechanical 60 ton capacity, adjustable stroke (pot mechanical 60 ton capacity, adjustable stroke (pot mechanical 60 ton capacity, adjustable stroke (no flaplock guard) ARKADIA PUNCHMATIC MODEL 20/20 NARKADIA PUNCHMATIC MODE					£ 210.00
with coolant E8912.00 S VERTICAL D ARBOGA MODEL U.2508 Table 22" x 10". Speeds 100–2900 rpm INDUMA MODEL VM/99 Table 49%" x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant Equipped with Equ			SD		
VERTICAL D ARBOGA MODEL U.2508 Table 22" x 10". Speeds 100—2900 rpm INDUMA MODEL V.M/49 Table 49% x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL V.M/60 Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL V.M/70 Table 55" x 15". Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/90 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL V.M/90 Table 86%" x 17%". Power feeds and rapids in all directions. Equipped with coolant Agents for A.JAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity, adjustable stroke for flaplack guard) ARKADIA PUNCHMATIC MODEL 20/20 ARKADIA BLANKING PUNCH PRESS MOD. ATTR6010 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 Bounched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with reciculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x		£8912 00	SD	NORTO! I FLY NO: 6	£ 250.00
D ARBOGA MODEL U.2508 Table 22" x 10". Speeds 100—2900 rpm INDUMA MODEL VM/49 Table 49%" x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL VM/70 Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant Equipped with coolant INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Equipped with peeds and rapids in all directions. Spind Equipped with Equipped with Equippe		20012.00	S	REMPSTONE 'TEN' PNEUMATIC	
Table 22" x 10". Speeds 100—2900 rpm				10 ton capacity, foot operated,	
INDUMA MODEL VM/49 Table 49%* x 10" 40 INT. Spindle speeds 40–1600 rpm. Power feeds and rapids in all directions. Equipped with coolant (NDUMA MODEL VM/90) Table 59" x 11" 50 INT. Spindle speeds 30–1500 rpm. Power feeds and rapids in all directions. Equipped with coolant (Equipped with coolant all directions. Equipped with coolant (Equipped with coolant all directions. Spindle speeds 30–1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant (Equipped wit				mounted on a stand	£ 632.00
Table 49%" x 10" 40 INT. Spindle speeds 40–1600 rpm. Power feeds and rapids in all directions. Equipped with coolant firections. Spindle speeds 30–1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant firections. Spindle speeds 30–1500 rpm. Equipped with speeds 30–1500 rpm. Equipped with spindle		£1254.00	S	SYXTO AIR HYDRAULIC BENCH PRESS	
lable 49%" x 10" 40 INT. Spindle speeds 40—1600 rpm. Power feeds and rapids in all directions. Equipped with coolant 170 power feeds and rapids in all directions. Equipped with coolant 170 power feeds and rapids in all directions. Equipped with coolant 170 power feeds and rapids in all directions. Equipped with coolant 170 power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant 170 power feeds and rapids in all directions. 50 INT. Spindle				6 ton capacity, guarded	£ 414.00
directions. Equipped with coolant NDUMA MODEL VM/60 Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Introduced with spindle speeds 30—1500 rpm. Equipped with coolant Introduced with spindle speeds 30—1500 rpm. Equipped with coolant Introduced with spindle speeds 30—1500 rpm. Equipped with coolant Introduced with spindle speeds 30—1500 rpm. Equipped with coolant E16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT BESSES CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke E4110.00 Open front mechanical 60 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKIND PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" CARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 ARKADIA PUNCH			S		
INDUMA MODEL VM/60 Table 59" x 11" 50 INT. Spindle speeds 30–1500 rpm. Power feeds and rapids in all directions. Equipped with coolant for INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Sindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL The Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with coolant for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearing so X & St Y traverses and repeat punching facility for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility for INDUMA MODEL Spindle speeds 30–1500 rpm. Equipped with recirculating bearings on X & Y trav				3 ton capacity, ungeared Bench Model,	
INDUMA MODEL VM/60 Table 59" x 11" 50 INT. Spindle speeds 30—1500 rpm. Power feeds and rapids in all directions. Equipped with coolant INDUMA MODEL VM/70 Table 75" x 15%. Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30—1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity press S SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke Open front mechanical 80 ton capacity, adjustable stroke Open front mechanical 80 ton capacity, adjustable stroke Open front mechanical 60 ton capacity, adjustable stroke Open front mechanical 80 ton capacity, adjustable stroke, Udal interlock guards SAWING SAWIN		£6291.00			£ 628.00
30–1500 rpm. Power feeds and rapids in all directions. Equipped with coolant D INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant Equipped with coola			S		
30–1500 rpm, Power feeds and rapids in all directions. Equipped with coolant £9627.00 D INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant £13001.00 D INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant £13001.00 D INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant £16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688.00 Open front mechanical 60 ton capacity, adjustable stroke COPPERSS & SHEAR MODEL RE.60 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 ANCADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punching facility ARKADIA PUNCHMATIC MODEL 20/20 ANCADIA PUNCHMATI				6 ton capacity, Pedestal Mounted.	
directions. Equipped with coolant D INDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant D INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant D INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity Agiustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 60 ton capacity, adjustable stroke in Glaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheete without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x					
DINDUMA MODEL VM/70 Table 75" x 15%". Power feeds and rapids in all directions. Spindle speeds 30–1500 rpm. Equipped with coolant DINDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES DICHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity for pressory adjustable stroke on taplock stroke on the chanical 60 ton capacity for pressory adjustable stroke for falplock guard) ARKADIA PUNCHMATIC MODEL 20/20 ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" Capacity 20 ton. Throat 20" Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x with a punching capacity of 160mm x with a punching capacity of 160mm x		£9627.00			£ 958.50
all directions. Spindle speeds 30—1500 rpm. Equipped with coolant £13001.00 INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant £16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke £4110.00 DPRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) £6745.00 ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 HORIZONTAL Capacity 10" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x			S		
all directions. Spindle speeds 30–1500 rpm. Equipped with coolant £13001.00 D INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant £16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) £6745.00 ARKADIA B LANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 70 ton, throat depth 510mm. Max. size speeded 100mm x 2mm. Max. size sheet without re-locating 1500 x S00mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x				18 ton capacity, adjustable stroke, Udal	
Equipped with coolant INDUMA MODEL VM/90 Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30–1500 rpm. Equipped with coolant Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity, adjustable stroke Open front mechanical 60 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					£1715.00
Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant £16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x		£13001.00			
Table 86%" x 17%". Power feeds and rapids in all directions. 50 INT. Spindle speeds 30—1500 rpm. Equipped with coolant £16283.00 Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x				Agents for CRESSEX, MARLCO and	
Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity adjustable stroke D PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 bt with a punching capacity of 160mm x E16283.00 SAWING BAND SD FORTE MODEL 250 HORIZONTAL Capacity 10" SD GOTTE MODEL 180. Automatic horizontal, capacity 7" SD QUALTERS & SMITH MODEL 180. Automatic horizontal, capacity 7" SD QUALTERS & SMITH MODEL 260 Horizontal, capacity 10" SD GOTTE STABLET STABLE					
Agents for AJAX, ASTRA, HARRISON and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity feels 8,8 HEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility fallows a punching facility fallows for the punching apacity of 160mm x 2 mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility fallows fallows for the punching apacity of 160mm x 2 mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility fallows fallows fallows for the punching apacity of 160mm x 2 mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility fallows fall					
and ELLIOTT RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity for education of the process	1500 rpm. Equipped with coolant	£16283.00	SAW	/ING	
RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity f 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x SD FORTE MODEL 250 HORIZONTAL Capacity 10" SD QUALTERS & SMITH MODEL 180 Horizontal, capacity 7" SD QUALTERS & SMITH MODEL 260 Horizontal, capacity 10" SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 9" SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" SD START	Agents for AJAX, ASTRA, HARRISON				
RESSES D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x	and ELLIOTT				
D CHURCHILL MODEL 37UC Double sided hydraulic 50 ton capacity f 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x			SD	FORTE MODEL 250 HORIZONTAL	
CHORCHILL MODEL 3/UC Double sided hydraulic 50 ton capacity £ 688,00 PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke Department mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20 but with a punching capacity of 160mm x Automatic horizontal, capacity 10" SD QUALTERS & SMITH MODEL 180A Automatic horizontal, capacity 7" £1999.00 OUALTERS & SMITH MODEL 260 Horizontal, capacity 10" \$D QUALTERS & SMITH MODEL 260A Automatic horizontal, capacity 7" £1999.00 SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" \$D QUALTERS & SMITH MODEL 260A Automatic horizontal, capacity 7" £1999.00 SD STARTRITE MODEL 200A Automatic horizontal, capacity 7" £1999.00 SD STARTRITE MODEL 200A Automatic horizontal, capacity 7" £1999.00 SD STARTRITE MODEL 200A Automatic horizontal, capacity 10" £2490.00 SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" £2490.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 £1018.00	PRESSES			Capacity 10"	£1070.00
Double sided hydraulic 50 ton capacity	CHURCHILL MODEL 37LIC		SD	FORTE MODEL 'FORTEMAT' BA.251	
PRESS & SHEAR MODEL RE.60 Open front mechanical 60 ton capacity, adjustable stroke DPRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x SOUNALTERS & SMITH MODEL 180A Automatic horizontal, capacity 7" C1999.00 Automatic horizontal, capacity 10" SD STARTRITE MODEL UMB.220 Horizontal, capacity 9" SD STARTRITE MODEL UMB.220 Horizontal, capacity 9" SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" SD GUALTERS & SMITH MODEL 180A Automatic horizontal, capacity 10" SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" SD STARTRITE MODEL UMB.220 Horizontal, capacity 10" SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" SD STARTRITE MEBA MODEL SM		£ 688 00		Automatic horizontal, capacity 10"	£3508.00
Open front mechanical 60 ton capacity, adjustable stroke £4110.00 D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) £6745.00 ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" £3445.00 ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		1 000,00	S	QUALTERS & SMITH MODEL 180	
adjustable stroke D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, Arguing and the facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, Arguing and the facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x				Horizontal, capacity 7"	£1020.00
D PRESS & SHEAR MODEL RE.80 Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) £6745.00 ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		£4110.00	SD		
Open front mechanical 80 ton capacity, adjustable stroke (no flaplock guard) £6745.00 ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" £3445.00 ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20 Horizontal, capacity 10" £1150.00 SD STARTRITE MODEL UMB.220 Horizontal, capacity 9" £ 952.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 Horizontal, capacity 10" £1018.00 SD STARTRITE MEBA MODEL SM.250 HORIZONTAL SM.250		L4110.00		Automatic horizontal, capacity 7"	£1999.00
adjustable stroke (no flaplock guard) £6745.00 ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" £3445.00 ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x			SD		
ARKADIA BLANKING PUNCH PRESS MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHING & NOTCHING MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		5674F 00			£1150.00
MOD. AT160/10 Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		10/45.00	SD		THE RES
Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					£2490.00
Capacity 20 ton. Throat 20" ARKADIA PUNCHMATIC MODEL 20/20 HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		COAAE OO	SD		
HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		£3445.00			£ 952.00
Capacity 20 ton, throat depth 510mm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		ıc	SD		
Capacity 20 ton, throat depth 5 lumm. Max. size punched 100mm x 2mm. Max. size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		IC .		7	£1018.00
size sheet without re-locating 1500 x 500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
500mm. Equipped with recirculating bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
bearings on X & Y traverses and repeat punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
punching facility £4997.00 ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
ARKADIA PUNCHMATIC MODEL 20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
20/20S HOLE PUNCHING & NOTCHING MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x		£4997.00			
MACHINE Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x	ARKADIA PUNCHMATIC MODEL				
Capacity 20 ton. As per Model 20/20 but with a punching capacity of 160mm x					
with a punching capacity of 160mm x					
with a punching capacity of 160mm x	Capacity 20 ton. As per Model 20/20 but				
		£5350.00			


SAV	/ING (continued)	PRICE EACH	SAV	/ING (Circular)	PRICE EACH
	BAND (continued)			CIRCULAR (continued)	
SD	STARTRITE MODEL MB.400 Horizontal, capacity 16"	£2686.00	S	GACO Capacity 10" x 4" sections, 10" x 3"	
SD	STARTRITE MODEL 12S1 Vertical, 11½" throat, 1 speed	£ 218.00	S	solids MEC BROWN	£1854.00
SD	STARTRITE MODEL 12S5 Vertical. 11½ throat, speeds			Ferrous and non ferrous capacity 2½" dia. o	:/w friction clutch £ 432.00
CD	840—4800 f.p.m.	£ 287.00		3 phase	1 432,00
SD	STARTRITE MODEL 12S10 Vertical. 11½" throat, speeds (10) 84–4800 f.p.m.	£ 342.00	SD	NOVA MAJOR TUBE SAW Ferrous and non ferrous capacity 2.3" Pedestal mounted. Equipped with	
SD	STARTRITE MODEL 14 RWH Vertical. 13½" throat, speeds (10) 50–		S	coolant and hydraulic vice PERRIS 300	£ 756.00
	1300 f.p.m. Equipped with hydraulic table feed, blade welder grinder and shear, chip blower and spotlight	£1121.00	Ĭ	Non ferrous capacity 4½" dia. Pedestal mounted	£ 640.00
SD	STARTRITE MODEL 14RF Vertical. 13½" throat, speeds (10)	C E1E 00	SD	SUPER BROWN Ferrous and non ferrous capacity 3" dia. Pedestal mounted. Equipped with	
SD	50–1300 f.p.m. STARTRITE MODEL 216H	£ 515.00		hydraulic vice	£ 756.00
	Vertical. 15½" throat, inf. variable speeds 50–3600 f.p.m. Equipped with hydraulic			Agents for MEDDINGS and EISELE HACK	
	table feed, blade welder, grinder and shear, chip blower and spotlight	£1911.00	S	KASTO MODEL HBS.150/170	
SD	STARTRITE MODEL 18T10 Vertical. 18" throat, speeds 56—3200 f.p.m.		SD	6" capacity, complete with coolant KASTO MODEL UBS.200	£ 935.00
SD	STARTRITE MODEL 18V10	2 002.00	SD	7.7/8" capacity, complete with coolant	£ 805.00
	Vertical, 18" throat, speeds 56—3200 f.p.m. Equipped with blade welder, grinder and	£ 852.50	SD	KASTO MODEL UBS.280 11" capacity, complete with coolant	£1465.00
SD	shear, chip blower and spotlight STARTRITE MODEL 20RWS Vertical. 20" throat, speeds 50—3000 f.p.m.		SD	KASTO MODEL EBS.320U 12.5/8" capacity, complete with coolant	£2945.00
	Equipped with blade welder, shear and grinder, chip blower and spotlight	£1056.00	S	QUALTERS & SMITH MODEL QSH.6 6" capacity, complete with coolant, 3 phase	£440.00
SD	STARTRITE MODEL 30RWS			1 phase	£ 480.00
	Vertical. 30" throat, speeds 50—3000 f.p.m. Equipped with rack and pinion table feed, blade welder, grinder and shear, chip		SD	QUALTERS & SMITH MODEL QSH.8 8" capacity, complete with coolant	£ 645.00
	blower and spotlight	£1124.00	SD	QUALTERS & SMITH MODEL QSH.10 10" capacity, complete with coolant	£ 979.00
S	ASTRA MERCURY		SD	WICKSTEED NO: 8 HYDRAMATIC 8" capacity, complete with coolant, work support stand and 1 shot lubrication	£ 850.00
	Capacity 3" tubes, speeds 3500 rpm. Portable	£ 94.00			2 000.00
SD	DE WALT TYPE M.210 RADIAL ARM		SHE	ETMETAL	
	Capacity in non ferrous 13" cross cut, 3" depth of cut. 1 phase	£ 270.00		BENDING ROLLS	
SD	DE WALT TYPE 1520 RADIAL ARM Capacity in non ferrous 13" cross cut,		SD	SAFAN MODEL PWM.2500/8 Capacity 2500mm x 8mm power operated	£5332.00
	3½" depth of cut. Equipped with inf. variable blade feed control and mist		SD	P & S TYPE PSR.50/16 Capacity 50" x 16g. Hand operated	£ 328.00
	coolant	£ 798.00		FOLDING	
			SD	ELGA MODEL BP.50/14 Hand operated Box & Pan Folder, capacity 50" x 14g	£ 904.00

dividing heads, surface plates, etc., by various manufacturers.

NEW MACHINE TOOLS AND SHEET METAL EQUIPMENT										
SHE	EET METAL (continued) P	RICE EACH		P	RICE EACH	SHE	ET METAL (continued)	PRICE EACH		PRICE EACH
	FOLDING (continued)			NIBBLING			PRESS BRAKES (continued)		TUBE BENDING	
SD	ELGA MODEL BP.80/14 Hand operated Box & Pan Folder, capacity 80" x 14g GUILLOTINES	£1140.00	SD	TRUMPF MODEL TAS.500 Throat depth 41". Speeds 600—1500rpm, shearing capacity 0.2". Equipped with inside circle cutting attachment	£2502.00		SAFAN MODEL SK.110—3100 HYDRAULIO DOWNSTROKING Capacity 3100mm x 110 tons. Equipped with positive mechanical depth stops, digital readou		S STAFFA MODEL OFB/1 Hydraulic, capacity 3/8"—3" Equipped with formers	£ 314.00
CD				IOTCHING			of depth, central front operated backgauge an		WELDING	
SD	ELGA MODEL ETS.40/16 Treadle operated, capacity 40" x 16g	£ 324.00		P & S UNI-NOTCH MODEL UNI.50/3 Capacity 6" x 1/8" P & S UNI-NOTCH MODEL 100/3	£1100.00		Agents for PEARSON, RUSHWORTH & KEETONA	£10678.00	SD MAX ARC TYPE 0/300 Single operator, oil cooled ARC Welder 300 amps	£ 236.00
S	ELGA MODEL ETS.50/16 Treadle operated, capacity 50" x 16g	£ 360.00	S	Capacity 4" x 1/8" ARKADIA MODEL 100/3	£ 944.00	S	SHEARING KEETONA TYPE KESMM UNIVERSAL HAND OPERATED		SD OXFORD TYPE RT.180 Arc Welder 180 amps	£ 136.00
SD	ELGA MECHANICAL MODEL 50/14 Capacity 50" x 14g	£1390.00		Capacity 4" x 1/8". Equipped with automatic lubrication system, pneumatically operated	£ 793.00	SD.	Capacity angle iron 1.3/8" x 3/16" SCOT GOLIATH MODEL 3LN HAND	£ 73.50	SD OXFORD TYPE RT.140 Arc Welder 140 amps with accessories	£ 101.00
SD	SAFAN HYDRAULIC MODEL VS.255/4 Capacity 2500mm x 4mm. Equipped with blade gap clearance adjustment, shadow line lighting, 2 front support arms, 2 spring loaded		SD	ARKADIA MODEL 130/2 Capacity 130mm x 2mm. Equipped with automatic lubrication system, pneumatically operated	£ 727.00	60	LEVER Capacity 1/8" mild steel sheet, 5/32" iron bar	£ 48.00	Agents for MERITUS, N.P.W., BRIT	TISH
	front stops, left & right hand squaring arm, front dial operated back gauge, high carbon high chrome blades	£6278.00	SD	ARKADIA MODEL 150/3 Capacity 6" x 6" x 1/8". Equipped with blades, adjustable material stops, adjustable	727.00	SD	SCOT GOLIATH MODEL 3RN HAND LEVER Capacity 1/8" mild steel sheet, 5/32" iron bar	£ 27.00	SD EPCO TONDRAULIC FLOOR CRA 1 ton capacity	£ 210.25
S	SAFAN HYDRAULIC MODEL VS.205/6 Capacity 2050mm x 6mm Equipped with blade gap clearance adjustment, shadow		S	blade gap, graduated internal stop and mounted on a pedestal ARKADIA MODEL 300/3	£1248.00	SD	SCOT GOLIATH MODEL 5RN HAND LEVER Capacity 3/16" mild steel, "" iron bar	£ 33.00	SD EPCO TWO TONDRAULIC FLOOR 2 ton capacity SD PLATYPUS MODEL P4H HAND	f 505.25
	line lighting, 2 front support arms, 2 spring loaded front stops, left & right hand squaring arms, front dial operated back gauge, high carbon high chrome		5	Capacity 12" x 12" x 10g. Equipped with blades, adjustable material stops, adjustable blade gap and mounted on a pedestal	£2441.00	SD.	SWAGING P & S UNIVERSAL SWAGING,		OPERATED STACKER TRUCK 4 cwt capacity Agents for TUSKAN fork lift trucks	£ 246.00
SD	SAFAN HYDRAULIC MODEL VS.255/6 Capacity 2550mm x 4mm. Equipped with	£7158.00	S	ARKADIA MODEL 250/6 Capacity 10" x 10" x ¼". Equipped with blades, adjustable material stops, adjustable		35	JENNYING & WIRING MACHINE MODEL CMZ.5 Throat depth 8½". Capacity 19g	£ 144.00	MISCELLANEOUS S CHAPLIN DRYSTORE CABINETS	S for
	blade gap clearance adjustment, shadow line lighting, 2 front support arms, 2 spring loaded front stops, left & right hand squaring arm, front dial operated back gauge, high carbon		SD	blade gap and mounted on a pedestal PRESS BRAKES SAFAN MODEL SK.25—1650 HYDRAULIC DOWNSTROKING	£3233.00	SD	P & S UNIVERSAL POWER OPERATED SWAGING, WIRING AND JENNYING MACHINE MODEL CMZ.7R		welding accessories SD SPENSTEAD DWARFLINE DUST CONTROL UNIT complete with ho	£ 80.00
	high chrome blades SAFAN HYDRAULIC MODEL VS.310/6 Capacity 3100mm x 6mm. Equipped with	£7790.00		Capacity 1650mm x 25 tons. Equipped with digital readout of depth, central front operated backgauge, front sheet supports	£4674.00		Throat depth 11". Capacity 14g UNIVERSAL STEELWORKERS	£ 627.00	spindle complete with hinged hoc	LISHING
	blade gap clearance adjustment, shadow line lighting, 2 front support arms, 2 spring loaded front stops, left & right hand squaring arm, front dial operated back gauge, high carbon		SD	SAFAN MODEL SK.35–2050 HYDRAULIC DOWNSTROKING Capacity 2050mm x 35 tons. Equipped with	24074.00	SD	PEDDINGHAUS MODEL 210/13 SUPER Capacity flats 6" x 5/8", angles 5" x ½", bar 1.5/8"	£6978.00	S ARKADIA MANLOVE SWARF SE Basket dia. 20", capacity 1.25 cu.ft All prices are exclusive	£1407.00
	high chrome blades	£8614.00		digital readout of depth, central front	05000 00	TAPF	PING		ACCESSORIES AND EQ	
SD	SAFAN HYDRAULIC MODEL HVS.310/1310 Capacity 3100mm x 16mm. Equipped with blade gap clearance adjustment, shadow line		S	operated backgauge, and front sheet supports SAFAN MODEL SK.50–2050 HYDRAULIC DOWNSTROKING Capacity 2050mm x 50 tons. Equipped with	15039.00	S SD	ASTRA Hand Operated, capacity 3BA-3/8" ASTRA Horizontal Capacity 3/16"	£ 256.20 £ 59.00	MAGNETIC CHUCKS:	Carbon High speed steel Eclipse Fimax
	lighting, 2 front support arms, 2 spring loaded front stops, left & right hand squaring arms, power operated backgauge, digital readout,		SD	digital readout of depth, central front operated backgauge, and front sheet supports SAFAN MODEL SK.50–2550 HYDRAULIC	£5930.00	S	HERKE SIZE 1 BENCH Capacity 9BA-¼". Equipped with tapping chuck	£ 286.35	BURNERD MULTISIZE COLLET CHUCKS:	Key Operated Lever Operated We also stock multisize
SD	SAFAN HYDRAULIC MODEL ES.205/4 Capacity 2050mm x 4mm. Equipped with	£13066.00	J.D	DOWNSTROKING Capacity 2550mm x 50 tons. Equipped with digital readout of depth, central front			MEDDINGS MODEL TB4/RC EADING	£ 746.00	CHUCKS:	collet sets EC & ED series 3 and 4 jaw 4" – 16" 200–600 g.p.h. 1 phase &
	centrally operated backgauge, blade gap adjustment, High carbon high chrome blades Agents for PEARSON, RUSHWORTH, MORG	£4994.00	SD	operated backgauge, and front sheet supports SAFAN MODEL SK.80-3100 HYDRAULIC DOWNSTROKING	£6589.00	SD	PISET MODEL 4SB Capacity 4"-4" pipe, 3/8"-1½" bolts. Speeds (3) 7)28 rpm	£ 932.00	CLARKSON AUTOLOCK CHUCKS:	3 phase 30, 40 or 50 INT — small and large
	& KEETONA			Capacity 3100mm x 80 tons. Equipped with positive mechanical depth stops, digital readour of depth, central front operated backgauge and front sheet supports						
	A.U			VAT					griding wheels, certiles, electric switches	to phase, Totally tables,

ARKADIA PUNCHMATIC

HOLE PUNCHING & NOTCHING MACHINE MODEL 20/20



Capacity Throat depth Max. size punched Punch ram adjustment Strokes per minute 45 Max. size sheet without re-locating Size of duplicator

Size of worktable

20 tons 510mm 100 x 2mm $0 - 10 \, \text{mm}$

900 x 500 mm 500 x 1500 mm 1800 x 750 mm

Machine equipped with a choice of 20 round punches up to 50 mm, re-circulating bearings on both longitudinal & cross traverses, repeat punching facility with adjustable stroke template clamps for repetition work, longitudinal & Cross slide clamping, plunger control for punch action, adjustable workpiece clamping levers, adjustable stripper plate, eccentric punch location lock, punch hole setting lever, adjustable air pressure gauge, workpiece skid balls, longitunal feed guide, die holder plate and a cross feed guide.

ALSO MODEL 40/30


Capacity Throat depth Max. size punched Punch ram adjustment Max. size sheet without re-locating Size of duplicator Size of worktable

40 tons 30" 160mm dia. x 3mm thick 40" x 60" 40" x 60" 174" x 42"

Machine equipped with:-

2 axis duplicating and template making equipment Stylus operated switch Separate foot switch Full size work tables, left and right Repeat punching facility.

ARKADIA MININI TYPE TH/PL 6-6



SPECIFICATION

Machine Capacity

Max, length to be ground Max. grinding width Max. grinding height

Working surface Length of tee slots Longitudinal traverse Feeds, inf. variable

Grinding Wheel

Standard dimensions Max, cross traverse Graduated cross feed Stepless adjustable motions Auto, vertical feed Rapid vertical traverse

24" x 24" 24.3/8"

24" × 20" 29" 29" 0 - 100 ft/min

14" x 5" x 2" 22"

0.039 - 0.984 in/min0-240 in/min 0.000197 - 0.00197" 20 in/min

Motor Horsepower

Grinding wheel motor 10 hp Vertical feed motor 10 hp Hydraulic pump motor 2.5 hp Côolant pump motor 0.25 hp

Equipment

Grinding wheel Grinding wheel arbor Grinding wheel extractor Wheel dresser without diamond

Rapid vertical feed unit with safety stop at the top of movement and automatic disengagement of wheel

Hydraulic braking safety unit at end of table traverse

Handwheel with graduated vernier for hand operation of vertical

Coolant pump and fittings with single magnetic filter

Automatic lubrication Grinding wheel balancing unit

Electro-hydraulic servo control unit for automatic vertical feed Standard 3 phase electrical equipment

